



COLOR SURFACING COLLECTION

STANDARD STOCKING COLOR

SSI SPECIAL ORDER (REQUIRES 150 ROLLS +/-10%)

■ STANDARD STOCKING COLOR

SSI SPECIAL ORDER (REQUIRES 150 ROLLS +/-10%)

■ STANDARD STOCKING COLOR

SSI SPECIAL ORDER (REQUIRES 150 ROLLS +/-10%)

■ STANDARD STOCKING COLOR

SSI SPECIAL ORDER (REQUIRES 150 ROLLS +/-10%)

■ STANDARD STOCKING COLOR

SSI SPECIAL ORDER (REQUIRES 150 ROLLS +/-10%)

■ STANDARD STOCKING COLOR

SSI SPECIAL ORDER (REQUIRES 150 ROLLS +/-10%)

■ STANDARD STOCKING COLOR

SSI SPECIAL ORDER (REQUIRES 150 ROLLS +/-10%)

■ STANDARD STOCKING COLOR

SSI SPECIAL ORDER (REQUIRES 150 ROLLS +/-10%)

■ STANDARD STOCKING COLOR

SSI SPECIAL ORDER (REQUIRES 150 ROLLS +/-10%)

■ STANDARD STOCKING COLOR

SSI SPECIAL ORDER (REQUIRES 150 ROLLS +/-10%)

■ STANDARD STOCKING COLOR

SSI SPECIAL ORDER (REQUIRES 150 ROLLS +/-10%)

■ STANDARD STOCKING COLOR

SSI SPECIAL ORDER (REQUIRES 150 ROLLS +/-10%)

■ STANDARD STOCKING COLOR

SSI SPECIAL ORDER (REQUIRES 150 ROLLS +/-10%)

■ STANDARD STOCKING COLOR

SSI SPECIAL ORDER (REQUIRES +/-10%)

■ STANDARD STOCKING COLOR

SSI SPECIAL ORDER (REQUIRES +/-10%)

■ STANDARD STOCKING COLOR

SSI SPECIAL ORDER (REQUIRES +/-10%)

■ STANDARD STOCKING COLOR

SSI SPECIAL ORDER (REQUIRES +/-10%)

■ STANDARD STOCKING COLOR

SSI SPECIAL ORDER (REQUIRES +/-10%)

■ STANDARD STOCKING COLOR

SSI SPECIAL ORDER (REQUIRES +/-10%)

■ STANDARD STOCKING COLOR

SSI SPECIAL ORDER (REQUIRES +/-10%)

■ STANDARD STOCKING COLOR

SSI SPECIAL ORDER (REQUIRES +/-10%)

■ STANDARD STOCKING COLOR

SSI SPECIAL ORDER (REQUIRES +/-10%)

■ STANDARD STOCKING COLOR

SSI SPECIAL ORDER (REQUIRES +/-10%)

■ STANDARD STOCKING COLOR

SSI SPECIAL ORDER (REQUIRES +/-10%)

■ STANDARD STOCKING COLOR

SSI SPECIAL ORDER (REQUIRES +/-10%)

■ STANDARD STOCKING COLOR

SSI SPECIAL ORDER (REQUIRES +/-10%)

■ STANDARD STOCKING COLOR

SSI SPECIAL ORDER (REQUIRES +/-10%)

■ STANDARD STOCKING COLOR

SSI SPECIAL ORDER (REQUIRES +/-10%)

SSI SPECIA



Antique Slate

© ecotorch © selfstickSACap ⊠ supercapSBS



Barkwood

30 ecotorch **30** selfstickSACap ⊠ supercapSBS



Black

oximes ecotorch oximes selfstickSACap oximes supercapSBS



Buff

⊠ ecotorch ⊠ selfstickSACap ⊠ supercapSBS



Green

SSI ecotorch SSI selfstickSACap ⊠ supercapSBS



Hickory



COLOR SURFACING COLLECTION



Pewter Gray

 \boxtimes ecotorch \boxtimes selfstickSACap \boxtimes supercapSBS



Red

SSI ecotorch SSI selfstickSACap ⊠ supercapSBS



Shakewood

⊠ ecotorch ⊠ selfstickSACap ⊠ supercapSBS



Weathered Wood

⊠ ecotorch ⊠ selfstickSACap ⊠ supercapSBS



Yosemite Green

⊠ ecotorch ⊠ selfstickSACap 🗓 supercapSBS





mbtechnology was founded in 1983 and specializes in the manufacturing of SBS modified bitumen roofing and underlayment systems. These include a suitable variety of systems which can be applied through the use of cold adhesives, heat welding, hot asphalt or self-adhesive.





ecotorch® is an innovative torch-applied, modified bitumen membrane that truly contributes to the environment and incorporates recycled tires into an SBS-modified bitumen formulation. ecotorch® is a more durable, dependable, and eco-friendly roofing membrane than any other APP or SBS-modified bitumen membrane. ecotorch® has superior end lap and metal adhesion compared to other torch membranes.



supercapSBS®

supercapSBS® is an SBS-modified, asphalt mineral-surfaced roll roofing membrane. supercapSBS® exhibits high multi-directional strength and excellent cold temperature flexibility in addition to elongation and recall properties far superior to that of traditional asphalt roofing membranes and unmodified MSR. supercapSBS® offers hot asphalt or cold adhesive application flexibility and is available with 10-year limited material warranty.



selfstickSACap®

selfstickSACap® is a premium self-adhesive, SBS-modified bitumen roofing membrane that is reinforced with either a polyester or fiberglass mat. It is specifically manufactured with a premium HT (High Tack) formulation to allow its application in cooler climates. This is ideal for areas where it is not feasible to use hot asphalt, cold adhesive, or torch applications. The **selfstickSACap®** system is used in conjunction with a nail base or a self-adhesive base/interply.



metalflexSBS® Cool White 24

metalflexSBS®Cool White 24 is manufactured with a white weatherresistant embossed aluminum foil surfacing and reinforced with a woven fiberglass mat. It is Class A fire-rated over a combustible deck with no slope restrictions.

metalflexSBS®Cool White 24 meets or exceeds Energy Star® requirements and can be used to comply with the 2016 California Title 24 Part 6 Cool Roof requirements. metalflexSBS®Cool White 24 reflects over 75% of solar energy away from the roof surface.





188 South Teilman Avenue, Fresno, California 93706-1334 Toll Free: 1-800-621-9281 / Ph: 559-233-2181 / Fx: 559-233-4607 Email: info@mbtechnology.com / www.mbtechnology.com









