

MB Liquid Flash

100% Solids Self Leveling Moisture Cure Sealant



For Professional Use Only

DESCRIPTION

- Self-Leveling technology for all seams, fasteners, ridge caps, flashings, and penetrations.
- Moisture curing multi-purpose one-component sealant/adhesive.
- Designed for Industrial uses requiring elasticity, high strength, and excellent adhesion.
- May be applied to surfaces at or below freezing temperatures. Make all attempts to remove frost.
- Performance at temperatures as low as -40 degrees F.
- Bonds to damp surfaces and is rain tolerant during cure.
- Cures to a waterproof tough flexible sealant.
- Low odor and minimal shrinkage.
- Non-staining and mildew resistant.
- UV resistant.
- VOC compliant.

RECOMMENDED USES

Industrial uses requiring high elasticity, high-strength and outstanding adhesion for a wide-range of substrates MB Liquid Flash bonds aggressively to steel, aluminum, ceramics, spray foam, styrofoam, EPS, glass, wood, fiberglass, concrete and coated metals.

| Property | Result |
|--|--------------------------------|
| Tensile Strength: | 200 psi |
| Elongation at break: | 500% |
| Hardness Shore A | 25 (5 day ambient cure) |
| Slump | Zero Slump |
| Application Temperature | 13 to 200 Degrees F. |
| Low Temp Flex | -20° F |
| Service Temp | -40°F to 200°F |
| Shelf Life (when stored @ 40°F to 80°F) | 12 months |

COLORS

White

APPLICATION

Can be applied to most surfaces without primer.

PACKAGING/SHIPPING INFORMATION

CONTAINER SIZE

10.3 and 28 fl. oz.
2 Gallon pail (7.6 liters)

SHIPPING CLASS

Class 55
Class 55

To the best of our knowledge all technical data contained herein is true and accurate as of the date of issuance and subject to change without prior notice. Used must contact MBTechnology to verify correctness before specifying or ordering. We guarantee our products to conform to the quality control standards established by MB Technology Products. We assume no responsibility for coverage, performance or injuries resulting from use. Liability if any, is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY MBTechnology EXPRESSED OR IMPLIED; STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

MBTechnology • 188 S Tielman Ave. • Fresno, CA 93706

www.MBTechnology.com • Phone 1-800-621-9281