

Product	Description	Usage	Application Method	Dimensions (nominal)	Coverage (sq/roll)	Weight lbs/roll (nominal)
			H Hot Asphalt C Cold Adhesive M Mechanically Fastened HW Heat Weld SA Self Adhering			
layfast SBS[®] Underlayment Tile, Shingle, & Metal Roofs. Meets ASTM D226 and ICC approved						
layfast SBS TU35	SBS modified asphalt underlayment/base. Reinforced with fiberglass mat.	SBS modified underlayment for use under tile, shingle roofs. Lays flat during application. Higher tensile, tear & weight compared to 30 & 40# felt.	M	3.31 ft (1m) x 64.75 ft (19.73m)	2	78
layfast SBS TU43	SBS modified asphalt underlayment/base. Reinforced with fiberglass mat.	SBS modified underlayment for use under tile, shingle roofs. Lays flat during application. Higher tensile, tear & weight compared to 30 & 40# felt. Ideal for jobs requiring a 40 # underlayment.	M	3.31 ft (1m) x 64.75 ft (19.73m)	2	88
layfast SBS TU70	SBS modified asphalt underlayment. Reinforced with fiberglass mat.	A heavy duty underlayment to be used under tile and metal roof. Ideal for applications where two layers of 30# is specified.	M	3.31 ft (1m) x 32.50 ft (9.91m)	1	68
layflat SBS[®] SBS Modified Base & Ply Sheet.						
layflat SBS LF25	SBS modified asphalt smooth membrane. Reinforced with fiberglass mat.	SBS modified base/ply. Minimizes wrinkles, buckles and fish mouths during application.	H, C, M	3.31 ft (1m) x 97.00 ft (29.56m)	3	85
layflat SBS LF60	SBS modified asphalt smooth membrane. Reinforced with fiberglass mat.	Premium SBS Modified smooth membrane used as an interply for hot & cold applied system.	H, C, M	3.31 ft (1m) x 49.50 ft (15.09m)	1.5	106
superflex SBS[®] SBS Modified Smooth Membrane and Cap Sheet.						
superflex SBS SF160PSA	SBS modified asphalt smooth membrane. Reinforced with polyester mat	A premium smooth SBS modified membrane used as interply / cap (with gravel) in 15-20 year guaranteed system. Polyester mat offers superior puncture and tear resistance.	H, C	3.30 ft (1m) x 33.33 ft (10.16m)	1	90
superflex SBS SF155PWH	SBS modified asphalt cap sheet. Reinforced with polyester mat	High puncture and tear resistance cap sheet. Can be mopped over base for 10 year warranted system.	H, C	3.30 ft (1m) x 33.33 ft (10.16m)	1	95
supercap SBS[®] Economy Grade SBS Modified Cap Sheet / Mineral Surfaced Rolled Roofing (MSR).						
supercap SBS SC85GWH	SBS modified fire rated Mineral Surfaced Roll Roofing available in 15 different popular shingle blends. Reinforced with fiberglass	Mineral Surfaced Roll Roofing, Tile Underlayment. Economical SBS Modified Cap Sheet.	H, C	3.31 ft (1m) x 33.33 ft (10.16m)	1	85
ECO TORCH SBS[®] Economical and Eco-Friendly (Containing SBS and Recycled Tire Rubber)						
ECO TORCH-G	SBS / Recycled Tire Modified heat welded, granulated membrane. Reinforced with polyester mat.	Rubberized granulated torch membrane. Can be used as cap sheet or flashing. Enhanced granule and end lap adhesion.	HW	3.31 ft (1m) x 33.33 ft (10.16m)	1	102
ECO TORCH-S	SBS / Recycled Tire Modified heat welded, smooth membrane. Reinforced with polyester mat.	Rubberized smooth torch membrane. Can be used as smooth ply for 2 ply system	HW	3.31 ft (1m) x 33.33 ft (10.16m)	1	85
fastorch SBS[®] Heat Welded Smooth, Granulated and Fire Rated Cap Sheet.						
fastorch SBS FT120GSA	SBS modified asphalt smooth membrane. Reinforced with fiberglass mat.	Smooth SBS modified membrane used as interply in two ply heat welded systems. Used in 10 & 15 year warranty.	HW	3.31 ft (1m) x 33.33 ft (10.16m)	1	88
fastorch SBS FT120PSA	SBS modified asphalt smooth membrane. Reinforced with polyester mat.	Smooth SBS modified membrane used as an interply in two ply heat welded systems. Polyester mat offers superior puncture and tear resistance. Used in 15 & 20 year warranty.	HW	3.30 ft (1m) x 33.33 ft (10.16m)	1	90
fastorch SBS FT160CSA	High performance SBS modified asphalt smooth membrane. Reinforced with a layer of polyester mat and fiberglass mat.	Dual reinforced smooth membrane used for heat welded application. Combination of polyester and fiberglass mat offers exceptional puncture and tensile strength. Projects utilizing this membrane qualify for MB Care program.	HW	3.33 ft (1m) x 33.33 ft (10.16m)	1	114
fireguard fastorch SBS FGFT160CWH	High performance fire rated SBS modified granulated membrane. Reinforced with a layer of polyester and fiberglass mat.	Premium dual reinforced fire rated cap membrane used as cap sheet for 20 year heat welded system. Combination of polyester and fiberglass mat offers exceptional puncture and tensile strength.	HW	3.33 ft (1m) x 33.33 ft (10.16m)	1	116

Product	Description	Usage	Application Method	Dimensions (nominal)	Coverage (sq/roll)	Weight lbs/roll (nominal)
			H Hot Asphalt C Cold Adhesive M Mechanically Fastened HW Heat Weld SA Self Adhering			
		Projects utilizing this cap sheet qualify for MB				
<i>fireguard fastorch</i> SBS FGFT160GWH	SBS modified asphalt fire rated granulated membrane. Reinforced with a layer of fiberglass mat.	Fire rated SBS modified cap membrane used for projects requiring 10-15 year warranty.	HW	3.31 ft (1m) x 33.33 ft (10.16m)	1	114
<i>fireguard fastorch</i> SBS FGFT160PWH	High performance fire rated SBS modified granulated membrane. Reinforced with a layer of polyester mat.	Premium polyester reinforced fire rated cap membrane used as cap sheet for 20 year heat welded system. Polyester mat offers exceptional puncture and tear strength.	HW	3.30 ft (1m) x 33.33 ft (10.16m)	1	113
metalflex SBS[®] SBS Modified Cap Membrane finished with embossed foil surfacing						
<i>metalflex</i> SBS MF160WAL	SBS modified asphalt cap membrane. Surfaced with embossed aluminum foil and reinforced with high tensile fiberglass scrim	Embossed Aluminum Foil surfacing offers exceptional reflectivity (0.86 C1549). CRRC & Energy Star Rated, Class A Fire Rated with no slope restriction. Ideal for roofs with slope over 2:12	HW	3.29 ft (1m) x 33.33 ft (10.16m)	1	103
<i>metalflex</i> SBS MF160WAL CoolWhite24	SBS modified asphalt cap membrane. Surfaced with embossed white aluminum foil and reinforced with high tensile fiberglass scrim. Meets the requirement for California "Title 24" Cool Roof, without the need for any additional coating.	Embossed Aluminum Foil surfacing offers exceptional reflectivity (0.78 C1549) and thermal emittance (0.84 C1371). CRRC Rated, Class A Fire Rated with no slope restriction. Ideal for roofs with slope over 2:12	HW	3.29 ft (1m) x 33.33 ft (10.16m)	1	103
fireguard SBS[®] Fire Rated (B) SBS Modified Cap Sheet.						
<i>fireguard</i> SBS FG90GWH	SBS modified asphalt fire rated granulated membrane. Reinforced with fiberglass mat.	Fire rated SBS modified cap membrane used for projects requiring 10-15 year warranty.	H, C	3.31 ft (1m) x 33.33 ft (10.16m)	1	90
<i>fireguard</i> SBS FG160CWH	High performance SBS modified asphalt granulated membrane. Reinforced with a layer of polyester mat and fiberglass mat for high puncture and tear strength.	Premium dual reinforced fire rated membrane used as a cap sheet for 20 year hot/cold applied system. Combination of polyester and fiberglass mat offers exceptional puncture and tensile	H, C	3.33 ft (1m) x 33.33 ft (10.16m)	1	110
<i>fireguard</i> SBS/SEBS FG160CWH	High performance SBS & SEBS modified asphalt granulated membrane. Addition of SEBS improves aging and U.V resistance. Reinforced with a layer of polyester mat and fiberglass mat for high puncture and tear strength.	Premium dual reinforced fire rated cap membrane used as cap sheet for 20 year hot / cold applied system. Combination of polyester and fiberglass mat offers exceptional puncture and tensile strength. Projects utilizing this cap sheet qualify for MB Care Program.	H, C	3.33 ft (1m) x 33.33 ft (10.16m)	1	110
<i>fireguard</i> SBS FG160PWH	SBS modified asphalt fire rated granulated membrane. Reinforced with polyester mat.		H, C	3.30 ft (1m) x 33.33 ft (10.16m)	1	105
Selfstick SA Cap						
<i>selfstick</i> SA Cap SA160PWH-HT	Premium SBS modified bitumen cap sheet, reinforced with polyester mat. Manufactured with a premium HT (High Tack) formulation. The sealing adhesive is protected on the bottom with a split-back release film. Available in 8 different shingle and solid granule colors.	Ideal for areas where it is not feasible to use hot asphalt, cold adhesive, or torch application. Selfstick SA Cap can be used for re-roofing, new construction, and repair of existing B.U.R. and modified bitumen systems.	SA	3.30 ft (1m) x 33.33 ft (10.16m)	1	95
<i>selfstick</i> SA Cap SA140GWH-HT Special run, non stock	Economical SBS modified bitumen cap sheet, reinforced with fiberglass mat. Manufactured with a premium HT (High Tack) formulation. The sealing adhesive is protected on the bottom with a split-back release film. Available in 8 different shingle	Ideal for areas where it is not feasible to use hot asphalt, cold adhesive, or torch application. Selfstick SA Cap can be used for re-roofing, new construction, and repair of existing B.U.R. and modified bitumen systems.	SA	3.31 ft (1m) x 33.33 ft (10.16m)	1	85
Ice & Moisture Block SBS Self Adhering ASTM D1970						
<i>ice & moisture block</i> SBS SA65G	Self-adhering SBS Modified Bitumen underlayment manufactured with a fiberglass mat and surfaced with fine mineral surfacing. The sealing adhesive is protected on the bottom with a split-back release film.	Used specially under steep sloped roofing systems to prevent moisture intrusion from ice dams and wind driven rain. Not suitable for metal roof.	SA	3.31 ft (1m) x 59.75 ft (18.21m)	2	79
<i>ice & moisture block</i> SBS SA65S	Self-adhering SBS Modified Bitumen underlayment / base manufactured with a	Used specially under steep sloped roofing systems to prevent moisture intrusion from ice dams and		3.31 ft (1m)		

Product	Description	Usage	Application Method	Dimensions (nominal)	Coverage (sq/roll)	Weight lbs/roll (nominal)
			H Hot Asphalt C Cold Adhesive M Mechanically Fastened HW Heat Weld SA Self Adhering			
	fiberglass mat and finished with a smooth sand finish. The sealing adhesive is protected on the bottom with a split-back release film.	wind driven rain. Also as a self adhesive base for APP & SBS membranes. Not suitable for metal roof.	SA	x 59.75 ft (18.21m)	2	65

Coating Meeting California Title 24 "Cool Roof" Requirement

<i>CO-24B</i> Base Coat	A high quality, versatile plasticizer free, single component, water-based, acrylic elastomer Base Coat for spray, brush or roller application.	CO-24B is designed as a general purpose coating for applications over metal, properly primed single ply and asphaltic surfaces such as asphalt emulsions. Check with your MBTechnology representative for primer recommendations.	Spray / Brush / Roller	Available In 5 & 55 Gallon Drums	Application Rate 1.50 gal / Square	5 Gallons 61 (lbs) 55 Gallons 700 (lbs)
<i>CO-24HT</i> Top Coat	Highest performance, plasticizer free, single component, water-based, 100% acrylic elastomeric coating for spray, brush or roller application.	CO-24HT is designed as a protective membrane for most roofing surfaces including galvanized metal, concrete, PVC, Hypalon, EPDM, polyurethane foam and primed smooth and granulated asphaltic surfaces. Check with your MBTechnology representative for primer	Spray / Brush / Roller	Available In 5 & 55 Gallon Drums	Application Rate 1.50 gal / Square	5 Gallons 61 (lbs) 55 Gallons 700 (lbs)

Shingle Starter Roll Meets ASTM D3909

<i>SR18G-Black</i>	Premium SBS Modified starter strip completely coated with SBS rubberized asphalt and surfaced with black ceramic granules. Requires 7-10 days lead time for	Starter SBS Roll is used for eave and rake starter material for composition roofing.	M	8" x 33.33 ft (10.16m)	0.22 (22 ft ²)	18
--------------------	---	--	---	------------------------------	-------------------------------	----

Cap Sheet Granule Colors Available: Other Colors Available Upon Request



Henry[®]